SAMPLING SOIL AND VEGETATION AT FACILITY SITES

Purpose

This Meteorology and Air Quality Group (MAQ) procedure describes the process for collecting soil, sediment, and vegetation samples from Material Disposal Area G (Area G) at TA-54, the Dual-Axis Radiographic Hydrodynamic Test (DARHT) facility at TA-15, and the Plutonium Facility at TA-55 as part of the Soil Monitoring Program, as mandated by DOE Order 450.1.

Scope

This procedure applies to the individual(s) assigned to collect samples from the facilities as part of the Facility Monitoring Program in MAQ.

In this procedure

This procedure addresses the following major topics:

Topic	See Page
General Information About This Procedure	2
Who Requires Training to This Procedure?	2
Worker Safety	4
Sample Collection	5
Chain-of-Custody for Samples	9
Records Resulting from This Procedure	10

Signatures

Prepared by:	Date:
Phil Fresquez, Environmental Surveillance Team Leader	<u>04/06/06</u>
Approved by:	Date:
Terry Morgan, QA Officer	<u>04/06/06</u>
Work authorized by:	Date:
Dianne Wilburn, Acting MAQ Group Leader	<u>04/06/06</u>

04/07/06

General information about this procedure

Attachments

This procedure has the following attachments:

		No. of
Number	Attachment Title	pages
1	Hazard Review	2
2	Environ Surveillance Team Chain-of-Custody Record	1
3	Soil Sampling Equipment and Diagram	3

History of revision

This table lists the revision history and effective dates of this procedure.

Revision	Date	Description Of Changes	
0	10/4/96	New document.	
1	3/99	Reformatted in accordance with LIR300-00-01,	
		Safe Work Practices.	
2	4/01	Added new Section 9.0, Training.	
3	4/02	Change in directorate.	
4	4/03	Team name change to Environmental Surveillance.	
5	5/12/04	Updated and reformatted document to conform with	
		MAQ procedures.	
6	4/11/05	Quick-change revision to convert HCP attachment to	
		HR.	
7	04/12/06	Quick-change revision to revise safety equipment	
		requirements in HR.	

Who requires training to procedure?

The following personnel require training before implementing this procedure:

• MAQ personnel assigned to collect samples

Training method

The training method for this procedure is **mentored** training by a previously-trained individual and is documented in accordance with the procedure for training (MAQ-024).

Annual retraining is required and will be by self-study ("reading") training.

Prerequisites

In addition to training to this procedure, the following training is also required prior to performing this procedure:

- First Aid
- Cardiopulmonary Resuscitation (CPR)
- RRES-ES-Field, "General Field Safety for All Employees"
- Site-specific training for Area G and DAHRT

General information, continued

Definitions specific to this procedure

Soil: Surface soil includes material from the 5-cm (0- to 2-in.) depth.

<u>Composite sample</u>: Samples composed of the five sub-samples taken from an area.

<u>Grab samples</u>: A single sample taken from a specific location at a given point in time.

<u>Sediments</u>: Surface runoff material from ephemeral and perennial stream bottoms.

<u>Vegetation</u>: Top growth material of plants.

References

The following documents are referenced in this procedure:

- MAQ-024, "Personnel Training"
- MAQ-026, "Deficiency Reporting and Correcting"
- MAQ-706, "Processing and Submitting Samples"
- RRES-ES-Field, "General Field Safety for All Employees"

Note

Actions specified within this procedure, unless preceded with "should" or "may," are to be considered mandatory guidance (i.e., "shall").

Worker Safety

Precautions and limitations

This document establishes the basic requirements for collecting soil samples. Work performed under this procedure by LANL personnel will occur only after required training to applicable documents has been completed and documented.

Safe work practices requirements

Project Personnel - A minimum of two people is required to go out in the field.

Personal Protective Equipment - For sampling, the following personal protective equipment must be worn: safety glasses, safety/field shoes, rubber gloves, and a hat.

Do not perform work under conditions you consider unsafe. Before beginning work described in this procedure, review safety needs and requirements, identify hazards, and develop hazard mitigation measures.

Sample Collection

Sampling information

<u>Types of Samples Collected</u> - Sampling occurs at three sites, Area G (TA-54), DARHT (TA-15), and the Plutonium Facility (TA-55), where three types of samples are collected:

- soil,
- sediments, and
- vegetation: understory (grasses, forbs, and/or shrubs) and overstory (tree).

Number of samples

The following table indicates the number of composite (c) or grab (g) samples that should be collected from each area. These numbers may vary according to funding provided by the customer. Drought conditions may also reduce the number of vegetation samples that can be collected.

_	TA-54	TA-15	TA-55
Soil	9 (c)	4 (c)	4 (c)
Sediment	N/A	4 (g)	
Vegetation	19 (c)	8 (c)	4 (c)

Equipment needed

Additional specific equipment required for going into the field is given in the procedure "General Field Safety for All Employees" (RRES-ES-Field).

The following equipment is required for all sampling:

- safety glasses
- rubber gloves
- tape measure
- permanent marker for labeling
- ice chest with blue ice
- zip-lock bags (gallon size)
- chain-of-custody forms (Attachment 2), tape

Additional equipment needed for each medium in addition to the above Soil Sampling

- stainless steel soil ring (10-cm diameter), top, and ring-spatula
- 3-lb hammer
- soap/water solution (for washing ring), water (rinsing), paper towels
- 500-mL & 125-mL polyethylene bottles (1 for each composite sample)

Sediment Sampling

- disposable polyethylene scoops
- 500-mL & 125-mL polyethylene bottles (1 for each composite sample)

Vegetation Sampling

gardening shears

Sample Collection, continued

for the field

Before leaving Check the condition of the vehicle and the fuel level. Identify a Point-of-Contact (providing pertinent information of destination, expected time-in, and how to notify field team). When leaving Los Alamos County, notify the group office to place you on travel status. Ensure that you have a working cell phone and a pager.

Steps for sampling soil

Sampling guidelines set by the American Society for Testing and Materials (ASTM) were used to develop the guidelines followed by the Environmental Surveillance Team. Each year, plan trips to facility sampling locations and perform the following steps:

Step	Action		
1	Locate the center of the sampling area, and place a clean 10-cm (4-in.) diameter stainless steel ring on the surface (see Attachment 3). Cover		
	the ring with the stainless steel top.		
2	Using a 3-lb hammer, drive the stainless steel ring 5 cm (2.0 in.) deep into the ground at the center and corners of a square area, 10-m (33-ft) per side. After driving the ring-sampler at each point, remove soil next to the soil ring-sampler, slip the spatula underneath the ring, and lift the sample. Place each of the five sub-samples into a 1-gallon zip-lock bag.		
3	Thoroughly mix the sub-samples in the zip-lock bag to form a composite sample. Pour the composite into a 125-mL polyethylene bottle (for heavy-metal analysis) and a 500-mL poly bottle (for radionuclide analysis).		
4	Seal each bottle with chain-of-custody tape. Label the bottle with the sample location, date, time, and your initials. Place each bottle into a 1-gallon zip-lock bag and then into ice chest.		
5	Complete a chain-of-custody form (Attachment 2) with the appropriate sampling information. Maintain proper chain-of-custody on the samples. See chapter <i>Chain-of-custody for samples</i> .		
6	Wash ring, spatula, and top with the soap/water solution, rinse with water, and then dry with paper towels.		
7	Once at the Lab, store the samples on ice or in a freezer until samples are shipped to the analytical laboratory (normally within two working days). Follow preparation and processing methods described in MAQ-706 ("Processing and Submitting Samples").		

Sample Collection, continued

Steps for sampling sediments

To collect sediment samples, perform the following steps:

Step	Action			
1	collect sediments to a depth of 5 cm (2 in.) in both a 125-mL (for he metal sampling) and a 500-mL (for radionuclide sampling) polyethylene bottle. • perennial streams: sample in dune buildup behind boulders i the main channel			
	ephemeral streams: sample in the center of the main channel			
2	Seal each bottle with chain-of-custody tape. Label the bottle with the sample location, date, time, and your initials. Place each bottle into a 1-gallon zip-lock bag.			
3	Place the bags in the cooler with ice for transport back to the laboratory. Complete a chain-of-custody form (Attachment 2) with the appropriate sampling information. Maintain proper chain-of-custody on the samples. See chapter <i>Chain-of-custody for samples</i> .			
5	Once at the lab, store the samples on ice or in a freezer until samples are shipped to the analytical laboratory (normally within two working days). Follow preparation and processing methods described in MAQ-706 (<i>Processing and Submitting Samples</i>).			

Sample Collection, continued

Steps for sampling vegetation

To collect vegetation samples, perform the following steps:

Step	Action		
1	Collect approximately three pounds of vegetation and place into a zip-		
	lock bag. Label the bag with the sample location, date, time, and your		
	initials.		
2	Place the bags in the cooler with ice for transport back to the		
	Laboratory. Complete a chain-of-custody form (Attachment 1) with the		
	appropriate sampling information. Maintain proper chain-of-custody		
	procedures for samples until they are shipped to the analytical		
	laboratory. See chapter Chain-of-custody for samples.		
3	Once at the Lab, store the samples on ice or in a freezer until samples		
	are processed (normally within two working days). Follow preparation		
	and processing methods described in MAQ-706 (<i>Processing and</i>		
	Submitting Samples).		

Chain-of-custody for samples

Maintaining custody of samples

A sample is physical evidence collected from a facility or the environment. Chain-of-custody must be documented for all samples used to demonstrate compliance. Verify that the possession and handling of samples is traceable at all times. A sample is considered in custody if it is one of the following:

- In one's physical possession.
- In one's view after being in one's physical possession.
- In one's physical possession and then locked up so that no one can tamper with it.
- Kept in a secure area where access is restricted to authorized and accountable personnel only.

NOTE: A secured area is an area that is locked, such as a room, cooler, vehicle, or refrigerator. If the area cannot be secured by locking, use a custody seal to secure the area or the sample container.

Transferring custody of samples

Whenever samples are transferred into the custody of another person or organization, complete the "relinquished by/received by" and "date" sections of the form (Attachment 2). These sections of the form must provide a complete history of custody of the samples from collection to transfer to the analytical laboratory.

If chain-ofcustody is broken

Whenever there is a break in the chain of custody of a sample, document the failure by initiating a deficiency report in accordance with the procedure for deficiencies (MAQ-026). [The deficiency process will document the occurrence, evaluate the potential impact (if any) on the samples, and propose a fix to prevent recurrence.]

Records resulting from this procedure

Records

The following records generated as a result of this procedure are to be submitted **within one year** as records to the records coordinator:

• Chain-of-Custody record

HAZARD REVIEW FOR FACILITY SOIL AND VEGETATION SAMPLING

Work tasks/Steps	Hazards, Concerns, and Potential accidents; Likelihood/ Severity	Controls, Preventive Measures (e.g., safety equipment, administrative controls, etc.)	Hazard Level from IMP 300-00-00 Hazard Grading Matrix
Travel to sampling sites in the field	Various field and outdoor hazards such as seasonal heat and cold extremes, wind, sun exposure, lightning, insects, reptiles, slips, falls, brush remote/moderate = low	Train to RRES-ES-Field, "General Field Safety for all Employees". Wear PPE that includes pants, long-sleeve shirt, safety glasses, steel toed safety shoes, and protective gloves.	Low
Collect samples around perimeter of TA-55.	Radionuclide contamination Occasional /moderate = low (Note: Knowledge of process of radionuclide contaminants at TA-55 show that they are within screening action levels and far below regulatory levels; there are no metals above background)	Follow all site-specific training and entry requirements.	
Enter DARHT to collect samples	Radionuclides and Be contamination remote/ moderate = low (Note: Process of knowledge of radionuclide and Be contaminants at the DARHT site show that they are within background concentrations)	Follow all site-specific training and entry requirements. Access control check-in required for DARHT. Note: because of the concern for Be by the DARHT H&S people, they may require that one soil sampling site {soil north} be sampled with a full face respirator if the ground is not moist.	

l	ENV-MAQ-711, R7
	Attachment 1, Page 2 of 2

Meteorology	and Air	Quality
Los Alamo	s National	Laboratory

Work tasks/Steps	Hazards, Concerns, and Potential accidents; Likelihood/ Severity	Controls, Preventive Measures (e.g., safety equipment, administrative controls, etc.)	Hazard Level from IMP 300-00-00 Hazard Grading Matrix
Enter Area G to collect samples	Radionuclide contamination remote/ moderate = low (Note: Knowledge of process of radionuclide contaminants at TA-54 show that they are within screening action levels and far below regulatory levels; there are no metals above background)	Follow all site-specific training and entry requirements. Facility-specific training is needed for Area G. Ensure youi are on the area's "Plan of the day".	
Collect soil samples according to steps for soil sample collection in the chapter "Collecting Samples"	Smashing fingers, toes, head and eyes with soil sampling tool. Occasional /moderate = low	Review MAQ-711 "Facility Soil and Vegetation Sampling" protocol for sampling procedures. Wear PPE.	Low
Collect sediment samples according to steps for sediment sample collection in the chapter "Collecting Samples"	Hammering injury (smashed fingers) & flying debris from use of ring and hammer Ergonomic injuries (repetitive motion) Occasional /moderate = low	Wear the minimum PPE as described above. Take a short break every hour.	
Collect vegetation samples according to steps for vegetation sample collection in the chapter "Collecting Samples"	Cutting fingers, dropping on toes, poking eyes with vegetation cutting shears Occasional /moderate = low	Use care when cutting with shears and clippers wear protective (Kevlar) gloves.	

Wastes or residual materials

Sample materials will be disposed by analytical laboratory.

Meteorology and Air Quality	ENV-MAQ-711, R7
Los Alamos National Laboratory	Attachment 1, Page 3 of 2


Emergency For cuts, perform Factions to take supervisor ASAP. in event of control failure

For cuts, perform First Aid as appropriate. Go to hospital for serious injuries. Go to HSR-2 for evaluation. Notify supervisor ASAP.


MAQ, Meteorology and Air Quality

Environmental Surveillance Team Chain-of-Custody Record This form is from MAQ-711 **Project Name** Facility Samplin Soils, sediments, and vegetation Project Contact _____ Facility Sampling Account Code Contact Phone No. _____ MS____ Cost _____ Center Program _____ Code **Analysis Requested** Date Time Station Name/Number Number of Remarks Collected Collected Samples Relinquished by (print and sign) Relinquished by (print and sign) Relinquished by (print and sign) Date Date Date Time Time Time Received by (print and sign) Received by (print and sign) Received by (print and sign) Date Date Date Time Time Time Samplers (print names and initial) Comments

Soil Sampling Equipment and Diagram



Soil Sampling Equipment and Diagram, Continued



Soil Sampling Equipment and Diagram, Continued

